2003 Author Index

Allen, C. B.	Steady and unsteady multiblock hovering rotor simulations	283–295
Althaus, J.	Auxiliary power system technology using a hydrodynamic clutch	143–148
Anand, R. B.	Effect of the turning angle on the flow and performance characteristics of long S-shaped circular diffusers	29–41
Ananthkrishnan, N.	Bifurcation analysis of inertia coupled roll manoeuvres of airplanes	75–85
Anderson, D.	Modification of a generalized inverse simulation technique for rotorcraft flight	61–73
Armstrong, K. B.	Efforts to standardize aerospace composite repairs, 1988–2003	223–236
Ashmore, D. R.	Hydrodynamic support and dynamic response for an inner-piloted bearing cage	19–28
Augello, G.	A two-level optimization feature for the design of aerospace structures	189–206
Avanzini, G.	Design and development of a vertical take-off and landing uninhabited aerial vehicle	169–178
Bannerjee, J. R.	The effect of laminate lay-up on the flutter speed of composite wings	115–122
Bushnell, D. M.	Aircraft drag reduction—a review	1–18
Carrera, E.	A two-level optimization feature for the design of aerospace structures	189–206
Cheung, C. W.	The effect of laminate lay-up on the flutter speed of composite wings	115–122
Clarke, T.	Desirable eigenstructure for good short-term helicopter handling qualities: the attitude command response case	43–55
Cooper, J. E.	On the use of control surface excitation in flutter testing	317–332
D'Angelo, S.	Design and development of a vertical take-off and landing uninhabited aerial vehicle	169–178
Davidson, G. G.	Learning from failures: design improvements using a multiple criteria decision-making process	207–216
de Matteis, G.	Design and development of a vertical take-off and landing uninhabited aerial vehicle	169–178
Dimitriadis, G.	On the use of control surface excitation in flutter testing	317–332
Ensor, J.	Desirable eigenstructure for good short-term helicopter handling qualities: the attitude command response case	43–55
Gethin, D. T.	Operating temperature of oil-lubricated medium-speed gears: numerical models and experimental results	87–106
Giannakopoulos, C.	Modelling the impacts of aircraft traffic on the chemical composition of the upper troposphere	237–243
Good, P.	Modelling the impacts of aircraft traffic on the chemical composition of the upper troposphere	237–243
Gratton, G.	The 'tumble' departure mode in weightshift-controlled microlight aircraft	149–166
Griffin, S. J.	Desirable eigenstructure for good short-term helicopter handling qualities: the attitude command response case	43–55
Gualtieri, N.	A two-level optimization feature for the design of aerospace structures	189–206
Guo, S. J.	The effect of laminate lay-up on the flutter speed of composite wings	115–122
Hess, R. A.	Designing for damage—robust flight control design using sliding mode techniques	245–261
Heyes, A. L.	On the roll-up of a trailing vortex sheet in the very near field	263–269
Hirtz, N.	Auxiliary power system technology using a hydrodynamic clutch	143–148
Hubbard, S. J.	On the roll-up of a trailing vortex sheet in the very near field	263–269
Labib, A. W.	Learning from failures: design improvements using a multiple criteria decision-making process	207–216
Law, K. S.	Modelling the impacts of aircraft traffic on the chemical composition of the upper troposphere	237–243
Leen, S. B.	Fatigue life prediction for a barrelled spline coupling under torque overload	123–142
Long, H.	Operating temperature of oil-lubricated medium-speed gears: numerical models and experimental results	87–106

© IMechE 2003

Lord, A. A.	Operating temperature of oil-lubricated medium-speed gears: numerical models and experimental results	87–106
Mannella, L.	A two-level optimization feature for the design of aerospace structures	189–206
Marquis, A. J.	On the roll-up of a trailing vortex sheet in the very near field	263–269
McColl, I. R.	Fatigue life prediction for a barrelled spline coupling under torque overload	123–142
McWilliam, S.	Hydrodynamic support and dynamic response for an inner-piloted bearing cage	19–28
Mehta, R. C.	Inverse venting problem for estimation of the discharge coefficient in a satellite launch vehicle	277–281
Newman, S.	The 'tumble' departure mode in weightshift-controlled microlight aircraft	149–166
Newman, S.	The fundamental configuration and design of the compound helicopter	297–315
Orchard, M.	The fundamental configuration and design of the compound helicopter	297–315
Paffoni, B.	Pressure and film thickness in a trochoidal hydrostatic gear pump	179–187
Rai, L.	Effect of the turning angle on the flow and performance characteristics of long S-shaped circular diffusers	29–41
Ratsimba, C. H. H.	Fatigue life prediction for a barrelled spline coupling under torque overload	123–142
Rimrott, F. J. P.	The principle of unidirectional collinearity of angular momenta	107–109
Roylance, B. J.	Operating temperatures of oil-lubricated medium-speed gears: numerical models and experimental results	87–106
Shallcross, D. E.	Modelling the impacts of aircraft traffic on the chemical composition of the upper troposphere	237–243
Singh, S. N.	Effect of the turning angle on the flow and performance characteristics of long S-shaped circular diffusers	29–41
Sinha, N. K.	Bifurcation analysis of inertia coupled roll manoeuvres of airplanes	75–86
Smith, D. A.	On the roll-up of a trailing vortex sheet in the very near field	263–269
Vetter, T. K.	Designing for damage—robust flight control design using sliding mode techniques	245–261
Wang, K.-Y.	Modelling the impacts of aircraft traffic on the chemical composition of the upper troposphere	237–243
Wells, S. R.	Designing for damage—robust flight control design using sliding mode techniques	245–261
Williams, E. J.	Hydrodynamic support and dynamic response for an inner-piloted bearing cage	19–28
Williams, E. J.	Fatigue life prediction for a barrelled spline coupling under torque overload	123–142
Wong, J.	On the use of control surface excitation in flutter testing	317–332
Wright, J. R.	On the use of control surface excitation in flutter testing	317–332

© IMechE 2003